Harlequin Studio

Harlequin Studio is a hard-wearing, slip-resistant, vinyl performance floor that features a lightweight closed-cell foam backing to provide protection against hard sub-floors, it is ideal as a multi-purpose dance or stage floor.

Installation: Harlequin Studio is specified for permanent or temporary installation, the joins are welded to form a continuous performance surface and is recommended for use in conjunction with a suitable Harlequin sprung floor.

Usage: Harlequin Studio is suitable for ballet, contemporary and modern dance. It is also used for aerobics, hip-hop, jazz and street dance.




All Harlequin vinyl floors are 100% recyclable.

Specification Guide

Material	Heterogeneous vinyl
Permanent or Portable	Both
Roll Lengths	10m, 15m, 18m, 20m, 25m, 30m
Roll Width	1.5m
Thickness	3mm
Weight	2.3kg/m ²
Finish	Smooth
Fire Rating	Bfl-s1 (EN 13501-1)
Warranty	10 years if installed by Harlequin
	5 years if installed by the customer
Impact Sound Reduction	6dB, with Harlequin Activity sprung floor 22dB
Fixing Type	Adhesive or Tape
Seams	Welded or Taped
Light Reflectance	180-2, 880-41, 890-20, 100-87
Gloss Level	Nominal 6
Lightfastness	>6
Recycled Content	23-30%
VOC Emissions	≤0.5mg/m³
Recyclability	100%
Underfloor Heating	Suitable for use with underfloor heating
Third Party Certification	Environmental Product Declaration A ⁺ LEED, BREEAM, REACH Compliant

Available Colours:

Black - 180



White - 100




Grey - 880



Dark Grey - 890

Light Grey - 156



















IB ANDERSEN ARTISTIC DIRECTOR







northern ballet

If you would like further information or advice please contact us on +44(0) 1892 514 888 or enquiries@harlequinfloors.com

HARLEQUIN www.harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. Harlequin @ is a registered trademark of British Harlequin plc. @ Harlequin Floors 01/2024